

SAFETY DATA SHEET

| Manufacturer | | | Company | GASTEC CORPORATION | |
|--|--------------|---|--------------------------|---|--|
| information | | | Address | 8-8-6 Fukayanaka, Ayase-city, Kanagawa 252-1195, Japan | |
| | | | Telephone | +81-467-79-3910 | |
| | | | FAX | +81-467-79-3979 | |
| SDS ID | SDS_122DL_03 | | Issue date | 31/May/2022 | |
| Product name | | Toluene Passive Dosi-Tube No.122DL | | | |
| Hazards identification | | This passive dosi-tube, when based on GHS and JIS Z 7252(2019), is corresponded to an article. Under normal use conditions, emits only a small amount of chemical substances, for example, trace amounts of chemical substances, and can be handled as not showing physical and chemical hazards or health hazards to operators. Therefore, this product does not fall under the GHS classification standard. | | | |
| Composition and information on ingredients | | A product made by impregnating alminium oxide($<10\%$) and porous silica gels(5-15%) with oleum($<10\%$), and sealing them in glass tubes. | | | |
| First-aid measures | | Eyes: If the filler enters the eye, immediately flush with plenty of water for at least 15 minutes and see a doctor. Skin: If the filler comes into contact with the skin, immediately wash with soapy water and flush with plenty of water. Inhalation: Not applicable. Ingestion: If the filler is swallowed, rinse the mouth immediately and see a doctor. | | | |
| Fire fighting measures | | No special measures are needed. | | | |
| Accidental release measures | | If the passive dosi-tube is broken, wear appropriate protective equipment to prevent the filler from adhering to or inhaling the skin or eyes. | | | |
| Handling and storage | | Handling When the ends of the detector tube are broken off to prevent injury, the detector tube is moved away from the eye. Do not touch with bare hands any cuts, fittings, or fillers in the event of breakage of the detector tube. | | | |
| Exposure control and protection measures | | Storage Not applicable. | Store in a colo | l/dark place | |
| Physical and chemical properties | | Appearance: A glass tube filled with reagents and sealed at both ends. Flash point: Not applicable. Ignition point: Not applicable. | | | |
| Stability and reactivity | | Stability: Not applicable. Reactivity: Not applicable. Conditions to avoid: Direct sunlight, high temperature, freezing should be avoided. Hazardous decomposition products: Not applicable. | | | |
| Toxicological information | | Filled material is made by adsorbing a small amount of chemicals to alminium oxide and porous silica gels, and there is no hazard information for this. The following describes the hazards to humans of the chemicals and carries as a pure sobstance. | | | |
| | | Alminium oxide: Acute toxicity: Oral—rat LD: Dermal—no c Inhalation(vap | 50:> 5,000 mg/kg lata | (IUCLID,2000) | |

| | Inhalation(dust,mist)-no data | | |
|---------------------------------|---|--|--|
| | Porous silica gel: Acute toxicity: Oral=rat LD50:>3,160 mg/kg (EPA pesticide ,1991), >3,300 mg/kg, >2,000 mg/kg, >5,000 mg/kg, >5,110 mg/kg (ECETOC JACC,2006)(SIDS,2006) Dermal=rabbit LD50 :> 2,000 mg/kg, >5,000 mg/kg (ECETOC JACC ,2006) (SIDS ,2006) Inhalation(dust,mist)=ratLC50(4-h exposure): >0.691 mg/L, > 2.22 mg/L, 0.09~0.84 mg/L, 1.65 mg/L (ECETOC JACC,2006) >2.08 mg/L (ECETOC JACC,2006)(SIDS,2006) Oleum: Acute toxicity: Oral=no data Dermal=no data Inhalation(dust,mist)=ratInhalationLC50:347pm/1H (= 86.7ppm/4H = 0.63 mg/L/4H) (assuming mist)(RTECS,1995) Sulfuric acid: Acute toxicity: Oral=rat LD50:2140mg/kg(SIDS,2001) Dermal=no data | | |
| | Inhalation(dust,mist)—ratLC50(4-h exposure):0.375mg/L(SIDS,2001) | | |
| Ecological information | No data | | |
| Disposal considerations | This passive dosi-tube does not contain any hazardous components. Should be disposed properly in accordance with local regulations. | | |
| Transport information | Avoid breakage of the passive dosi-tube due to dropping, pressurization, bending, etc. UN number: Not applicable UN Classification: Not applicable IATA: Not applicable Poisonous and Deleterious Substances Control Law: Not applicable Fire Defense Law: Not applicable Marine Regulation Information: Not applicable | | |
| Japanese regulatory information | Industrial Safety and Health Law: Hazardous substance No. 189, 165-2(Article 57-2) | | |
| Other information | References : Chemical Risk Information Platform (CHRIP): NITE Safety website in the workplace of the Ministry of Health, Labour and Welfare This data sheet is provided to businesses that handle hazardous chemical products as reference information for ensuring safe handling. With reference to this, business operators are requested to understand that they need to take appropriate measures in accordance with the actual conditions of individual handling, etc. at their own responsibility, and then use them. This data sheet is prepared based on JIS Z 7253(2019). The contents of this report have been prepared based on the latest information as of the date of revision, but if new information is obtained, it may be added or corrected. | | |
| | This data sheet is not a guarantee of safety. | | |