

SAFETY DATA SHEET

Manufacturer information			Company	GASTEC CORPORATION	
mormation			Address	8-8-6 Fukayanaka, Ayase-city, Kanagawa 252-1195, Japan	
			Telephone	+81-467-79-3910	
			FAX	+81-467-79-3979	
SDS ID	SDS_132D_03		Issue date	31/May/2022	
Product name		Trichloroethylene Passive Dosi-Tube No.132D			
Hazards identification		This passive dosi-tube, when based on GHS and JIS Z 7252(2019), is corresponded to an article. Under normal use conditions, emits only a small amount of chemical substances, for example, trace amounts of chemical substances, and can be handled as not showing physical and chemical hazards or health hazards to operators. Therefore, this product does not fall under the GHS classification standard.			
Composition and information on ingredients		A product made by impregnating alminium oxide($<5\%$) and porous silica gels(5-15%) with sulfuric acid($<5\%$), lead(IV) oxide($<1\%$) and diffuser(PE), and sealing them in glass tubes.			
First-aid mea	sures	and see a doctor Skin: If the filler plenty of water. Inhalation: Not a	or. comes into contact wi	mediately flush with plenty of water for at least 15 minutes the the skin, immediately wash with soapy water and flush with see the mouth immediately and see a doctor.	
Fire fighting measures		No special measures are needed.			
Accidental release measures		If the passive dosi-tube is broken, wear appropriate protective equipment to prevent the filler from adhering to or inhaling the skin or eyes.			
Handling and storage		Handling	When the ends of the detector tube are broken off to prevent injury, the detector tube is moved away from the eye. Do not touch with bare hands any cuts, fittings, or fillers in the event of breakage of the detector tube.		
		Storage	Store in the re	frigerator	
Exposure control and protection measures		Not applicable.			
Physical and chemical properties		Appearance: A glass tube filled with reagents and sealed at both ends. Flash point: Not applicable. Ignition point: Not applicable.			
Stability and reactivity		Stability: Not applicable. Reactivity: Not applicable. Conditions to avoid: Direct sunlight, high temperature, freezing should be avoided. Hazardous decomposition products: Not applicable.			
Toxicological information		Filled material is made by adsorbing a small amount of chemicals to alminium oxide and porous silica gels, and there is no hazard information for this. The following describes the hazards to humans of the chemicals and carries as a pure sobstance.			
		Alminium oxide: Acute toxicity: Oral — rat LD50:> 5.000 mg/kg (IUCLID.2000)			

Acute toxicity: Oral—rat LD50:> 5,000 mg/kg (IUCLID,2000)

Dermal—no data Inhalation(vapor)—no data Inhalation(dust,mist)—no data

```
> 3,300 \text{ mg/kg}, > 2,000 \text{ mg/kg}, > 5,000 \text{ mg/kg},
                                                        > 5,110 mg/kg (ECETOC JACC,2006)(SIDS,2006)
                                             Dermal—rabbit LD50 :> 2,000 mg/kg, > 5,000 mg/kg
                                                                      (ECETOC JACC ,2006) (SIDS ,2006)
                                             Inhalation(dust,mist)—ratLC50(4-h exposure):
                                                         >0.691 \text{ mg/L}, > 2.22 \text{ mg/L},
                                                               0.09~0.84 mg/L, 1.65 mg/L (ECETOC JACC,2006)
                                                              >2.08 mg/L (ECETOC JACC,2006)(SIDS,2006)
                                          Lead(IV) oxide:
                                            Acute toxicity: Oral - no data
                                                    Dermal-no data
                                                    Inhalation - no data
                                          Sulfuric acid:
                                            Acute toxicity: Oral—rat LD50: 2140mg/kg (SIDS, 2001)
                                                    Dermal-no data
                                                    Inhalation (dust) — ratLC50(4-h exposure): 0.375mg/L (SIDS,2001)
Ecological information
                                          No data
Disposal considerations
                                          This passive dosi-tube contains 13.86mg of lead. Should be disposed properly in accordance
                                          with local regulations.
Transport information
                                          Avoid breakage of the passive dosi-tube due to dropping, pressurization, bending, etc.
                                          UN number: Not applicable
                                          UN Classification: Not applicable
                                          IATA: Not applicable
                                          Poisonous and Deleterious Substances Control Law: Not applicable
                                          Fire Defense Law: Not applicable
                                          Marine Regulation Information: Not applicable
Japanese regulatory information
                                          Industrial Safety and Health Law: Hazardous substance No.189, 165-2, 411, 613(Article 57-2)
                                          PRTR: 1-305 Lead
                                          References:
Other information
                                          Chemical Risk Information Platform (CHRIP): NITE
                                          Safety website in the workplace of the Ministry of Health, Labour and Welfare
                                          This data sheet is provided to businesses that handle hazardous chemical products as reference
                                          information for ensuring safe handling. With reference to this, business operators are
                                          requested to understand that they need to take appropriate measures in accordance with the
                                          actual conditions of individual handling, etc. at their own responsibility, and then use them.
                                          This data sheet is prepared based on JIS Z 7253(2019). The contents of this report have been
                                          prepared based on the latest information as of the date of revision, but if new information is
                                          obtained, it may be added or corrected.
                                          This data sheet is not a guarantee of safety.
```

Oral—rat LD50:>3,160 mg/kg (EPA pesticide,1991),

Porous silica gel: Acute toxicity: