

SAFETY DATA SHEET

Manufacturer information		Company		GASTEC CORPORATION	
			Address	8-8-6 Fukayanaka, Ayase-city, Kanagawa 252-1195, Japan	
			Telephone	+81-467-79-3910	
			FAX	+81-467-79-3979	
SDS ID	SDS_233_03		Issue date	31/May/2022	
Product name		Chloropicrin Detector Tube No.233			
Hazards identification		This detector tube, when based on GHS and JIS Z 7252(2019), is corresponded to an article. Under normal use conditions, emits only a small amount of chemical substances, for example, trace amounts of chemical substances, and can be handled as not showing physical and chemical hazards or health hazards to operators. Therefore, this product does not fall under the GHS classification standard.			
Composition and information on ingredients		Pretreatment tube: A product made by impregnating porous silica gels(<10%) with chromium(VI) oxide(< 0.1%) and oleum(< 5%), and sealing them in glass tubes. Detector tube: A product made by impregnating porous silica gels(<10%) with reagent(< 0.1%), and sealing them in glass tubes.			
First-aid measures		Eyes: If the filler enters the eye, immediately flush with plenty of water for at least 15 minutes and see a doctor. Skin: If the filler comes into contact with the skin, immediately wash with soapy water and flush with plenty of water. Inhalation: Not applicable. Ingestion: If the filler is swallowed, rinse the mouth immediately and see a doctor.			
Fire fighting measures		No special measures are needed.			
Accidental release measures		If the detector tube is broken, wear appropriate protective equipment to prevent the filler from adhering to or inhaling the skin or eyes.			
Handling and storage		Handling	When the ends of the detector tube are broken off to prevent injury, the detector tube is moved away from the eye. Do not touch with bare hands any cuts, fittings, or fillers in the event of breakage of the detector tube.		
		Storage	Store in a cold/	dark place	
Exposure control and protection measures		Not applicable.			
Physical and chemical properties		Appearance: A glass tube filled with reagents and sealed at both ends. Flash point: Not applicable. Ignition point: Not applicable.			
Stability and reactivity		Stability: Not applicable. Reactivity: Not applicable. Conditions to avoid: Direct sunlight, high temperature, freezing should be avoided. Hazardous decomposition products: Not applicable.			
Toxicological information		Filled material is made by adsorbing a small amount of chemicals to porous silica gels, and there is no hazard information for this. The following describes the hazards to humans of the chemicals and carries as a pure sobstance.			
		Porous silica gel: Acute toxicity:			

```
> 5,110 mg/kg (ECETOC JACC,2006)(SIDS,2006)
                                            Dermal—rabbit LD50 :> 2,000 mg/kg, > 5,000 mg/kg
                                                                    (ECETOC JACC ,2006) (SIDS ,2006)
                                            Inhalation(dust,mist)—ratLC50(4-h exposure):
                                                        >0.691 \text{ mg/L}, > 2.22 \text{ mg/L},
                                                              0.09~0.84 mg/L, 1.65 mg/L (ECETOC JACC,2006)
                                                             >2.08 mg/L (ECETOC JACC,2006)(SIDS,2006)
                                         Oleum:
                                           Acute toxicity:
                                            Oral-no data
                                             Dermal - no data
                                            Inhalation(dust,mist)—ratInhalationLC50:347ppm/1H
                                                                         (= 86.7 \text{ppm}/4\text{H} = 0.63 \text{ mg/L}/4\text{H})
                                                                             (assuming mist) (RTECS, 1995)
                                         Sulfuric acid:
                                           Acute toxicity:
                                            Oral - rat LD50: 2140mg/kg(SIDS, 2001)
                                            Dermal—no data
                                            Inhalation(dust,mist)—ratLC50(4-h exposure): 0.375mg/L(SIDS,2001)
                                         Chromium(VI) oxide:
                                           Acute toxicity:
                                            Oral—rat LD50:52-113mg/kg (EU-RAR,2005)
                                            Dermal—rabbit LD50:30mg Cr (VI) /kg (CrO3 equivalent:57.7 mg/kg)
                                                             (CICAD 78,2013/ATSDR, 2012)
                                            Inhalation(dust,mist) — ratLC50(4-h exposure): 0.217mg/L (EU-RAR,2005)
                                         No data
Ecological information
Disposal considerations
                                         This detector tube does not contain any hazardous components. Pretreatment tube contains
                                         2.02mg of hexavalent chromium. Should be disposed properly in accordance with local
                                         regulations.
Transport information
                                         Avoid breakage of the detector tube due to dropping, pressurization, bending, etc.
                                         UN number: Not applicable
                                         UN Classification: Not applicable
                                         IATA: Not applicable
                                         Poisonous and Deleterious Substances Control Law: Not applicable
                                         Fire Defense Law: Not applicable
                                         Marine Regulation Information: Not applicable
Japanese regulatory information
                                         Industrial Safety and Health Law: Hazardous substance No.165-2(Article 57-2)
                                         References:
Other information
                                         Chemical Risk Information Platform (CHRIP): NITE
                                         Safety website in the workplace of the Ministry of Health, Labour and Welfare
                                         This data sheet is provided to businesses that handle hazardous chemical products as reference
                                         information for ensuring safe handling. With reference to this, business operators are
                                         requested to understand that they need to take appropriate measures in accordance with the
                                         actual conditions of individual handling, etc. at their own responsibility, and then use them.
                                         This data sheet is prepared based on JIS Z 7253(2019). The contents of this report have been
                                         prepared based on the latest information as of the date of revision, but if new information is
                                         obtained, it may be added or corrected.
                                         This data sheet is not a guarantee of safety.
```

Oral - rat LD50: > 3,160 mg/kg (EPA pesticide ,1991),

> 3,300 mg/kg, > 2,000 mg/kg, > 5,000 mg/kg,

